


DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq Yd:	50 sq yd minimum
Surface Texture:	Level Patterned Cut
Gauge:	1/10 (39.37 rows per 10 cm)
Tufted Pile Weight:	36 oz/yd² (1221 g/m²)
Finished Pile Thickness:	.184" (4.67 mm)
Stitches Per Inch:	13.3 (52.36 per 10 cm)
Dye Method:	Precision Dyed Injection
Fiber Type:	Colorstrand® Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	7,043
Weight Density:	253,565
Backing Material:	Weldlok®
Width:	12' width (3.66 m)
Pattern Repeat:	24" (W) x 24" (L) SM



851
Golden Truss
Quickship Available

SUSTAINABILITY

Pre-Consumer Recycled Content:	33%
NSF 140:	Weldlok - NSF 140 Gold
Indoor Air Quality:	CRI Green Label Plus GLP6678
Declare Label:	Declared Red List Free

PERFORMANCE

Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Severe

SERVICE

Warranties:	Lifetime Limited Wear Warranty, Lifetime Static
-------------	--