


DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Tufted Pile Weight:	17.0 oz. per sq. yd. (576 g/m²)
Finished Pile Thickness:	.116" (2.95 mm)
Stitches Per Inch:	12.3 (48.43 per 10 cm)
Dye Method:	Solution Dyed / Yarn Dyed
Fiber Type:	Colorstrand® Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	5,276
Weight Density:	89,692
Backing Material:	Weldlok®
Width:	12' width (3.66 m)
Pattern Repeat:	0.8" (W) x 0.9" (L)

SUSTAINABILITY

Pre-Consumer Recycled Content:	52%
NSF 140:	Weldlok - NSF 140 Gold
Indoor Air Quality:	CRI Green Label Plus GLP8216
Declare Label:	Declared Red List Free

PERFORMANCE

Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Severe

SERVICE

Warranties:	10 Year Limited Wear Warranty, 10 Year Static
-------------	--



358
Scientist
Quickship Available



689
Architect
Quickship Available



859
Composer
Quickship Available



862
Educator
Quickship Available



883
Scholar
Quickship Available



884
Philosopher
Quickship Available



955
Archaeologist
Quickship Available



983
Mathematician
Quickship Available



999
Writer
Quickship Available